



International Limited | Hong Kong

BRAND: BIOD PRO

Deep Cycle Batteries

01.01.2025

Note: Technical specifications are subject to change without prior notice. The table provides standard characteristics; however, battery weight and dimensions may vary depending on regional regulations or specific customer requirements. For orders and inquiries, please contact us at hello@tevo.com.hk

Model	Industry Ref.	Nominal Voltage (V)	Nominal Capacity (AH/20HR)	Battery Dimension				Weight (Approx.) kg	Terminal Type
				Length	Width	Height	Total Height		
				mm	mm	mm	mm		
DC200-6	27	6	200	306	169	220	226	30	T5
DC220-6	27	6	220	306	174	220	226	32.2	T5
DC224-6	GC2	6	224	260	180	245	251	29.8	T5
DC245-6	(DIN)	6	245	244	190	275	275	30	T5/AP
DC335-6	902/J305	6	335	295	178	346	366	46	DT/T5/AP
DC400-6	L16	6	400	295	179	404	424	55.7	DT/T5/AP
DC200-8	GC8H	8	200	260	182	295	299	37.6	T5
DC24-12	N/A	12	24	167	175	125	125	8	T2
DC26-12	N/A	12	26	167	175	125	125	8.3	T2
DC26-12S	N/A	12	26	166	126	174	174	8.4	T2
DC35-12	U1	12	35	196	131	155	167	10.5	T3
DC40-12	U1L	12	40	198	166	174	174	14.2	T2
DC55-12	22NF	12	55	229	138	208	212	16	T3
DC65-12	93	12	65	351	167	176	176	23.6	T3
DC70-12	24	12	70	260	169	211	215	24	T3
DC85-12	24	12	85	260	169	211	215	25.1	T3
DC90-12	27	12	90	307	169	211	215	28.2	T3
DC105-12	27	12	105	307	169	211	215	30.2	T3
DC115-12	31	12	115	331	175	214	218	32.9	T4
DC115-12S	31	12	115	328	172	214	220	32.7	T4
DC120-12	N/A	12	120	407	174	210	240	38.2	T5
DC135-12	N/A	12	135	341	173	281	287	39.2	T5
DC150-12	N/A	12	150	484	171	241	241	44.5	T4

DC160-12	N/A	12	160	484	171	241	241	45.5	T4
DC180-12	4D	12	180	532	206	216	221	56	T4
DC200-12	4D	12	200	522	240	219	224	58.4	T4
DC210-12	4D	12	210	532	206	216	221	57.8	T4
DC220-12	4D	12	220	522	240	219	224	65	T4
DC240-12	8D	12	240	520	269	203	208	71	T5
DC260-12	8D	12	260	521	269	220	224	77	T5