



International Limited | Hong Kong

BRAND: BIOD PRO

General VRLA (AGM) Batteries

Note: Technical specifications are subject to change without prior notice. The table provides standard characteristics; however, battery weight and dimensions may vary depending on regional regulations or specific customer requirements. For orders and inquiries, please contact us at hello@tevo.com.hk

01.01.2025

Model	Nominal Voltage (v)	Nominal Capacity (Ah/20HR)	Battery Dimension				Weight (Approx) kg	Terminal Type
			Length	Width	Height	Total Height		
			mm	mm	mm	mm		
BD432	4	3.2	90	34	60	66	0.42	F1
BD445	4	4.5	47	47	100	106	0.5	F1
BD460	4	6	70	47	100	106	0.65	F1
BD612	6	1.2	97	24	52	58	0.3	F1
BD623	6	2.3	43	37	76	76	0.3	C
BD628	6	2.8	66	33	97	103	0.53	F1
BD632	6	3.2	134	35	61	67	0.65	F1
BD640P	6	4	194	25	62	62	0.69	Plug
BD640	6	4	70	47	100	106	0.65	F1
BD640C	6	4	70	47	100	106	0.68	C
BD645	6	4.5	70	47	100	106	0.72	F1
BD645C	6	4.5	70	47	100	106	0.73	C
BD650	6	5	70	47	100	106	0.8	F1
BD670	6	7	151	34	94	100	1.05	F1/F2
BD6100	6	10	151	50	94	100	1.5	F1/F2
BD6120	6	12	151	50	94	100	1.65	F1/F2
BD61000	6	100	194	170	205	212	16.5	T4
BD61500	6	150	260	180	245	252	23.5	T5
BD61800	6	180	306	164	220	225	28.6	T5
BD62000	6	200	240	185	275	275	32.5	T5
BD62250	6	225	320	176	225	230	30.5	T5
BD832	8	3.2	134	36	63	66	0.79	F1
BD1208	12	0.8	96	25	62	62	0.34	Plug

BD1213	12	1.3	97	43	52	58	0.5	F1
BD1220	12	2	178	35	61	67	0.8	F1
BD1220A	12	2	70	47	100	106	0.75	F1
BD1223	12	2.3	178	35	61	67	0.9	F1
BD1223C	12	2.3	182	24	61	61	0.7	C
BD1223CA	12	2.3	201	24	62	62	0.74	C
BD1226	12	2.6	70	47	100	106	0.8	F1
BD1229	12	2.9	79	56	98	104	1.05	F1
BD1232	12	3.2	134	67	61	67	1.3	F1
BD1240	12	4	90	70	100	106	1.35	F1/F2
BD1242	12	4.2	195	47	70	76	1.43	F1/F2
BD1245	12	4.5	90	70	100	106	1.45	F1/F2
BD1250	12	5	90	70	100	106	1.5	F1/F2
BD1260	12	6	151	50	94	100	1.8	F1/F2
BD1265	12	6.5	151	65	94	100	1.9	F1/F2
BD1270	12	7	151	65	94	100	2	F1/F2
BD1272	12	7.2	151	65	94	100	2.1	F1/F2
BD1275	12	7.5	151	65	94	100	2.2	F1/F2
BD1280	12	8	151	65	94	100	2.3	F1/F2
BD1285	12	8.5	151	65	94	100	2.5	F1/F2
BD1290	12	9	151	65	94	100	2.6	F1/F2
BD12100	12	10	151	99	95	101	3	F1/F2
BD12100A	12	10	151	65	111	117	2.75	F1/F2
BD12120	12	12	151	99	94	100	4	F1/F2
BD12170	12	17	181	77	167	167	5	L1/T1
BD12180	12	18	181	77	167	167	5.4	L1/T1
BD12200	12	20	181	77	167	167	6	L1/T1
BD12220	12	22	181	77	167	167	6.3	L1/T1
BD12240	12	24	166	175	125	125	7.3	L6/T2
BD12240A	12	24	165	125	175	182	7.5	L8
BD12260	12	26	166	175	125	125	8.3	L6/T2
BD12280	12	28	165	125	175	175	9.3	T2
BD12330	12	33	195	130	155	158	10.3	L7/T3
BD12380	12	38	197	165	170	170	12.4	T2/L3
BD12400	12	40	197	165	170	170	12.8	T2/L3
BD12450	12	45	197	165	170	170	13.5	T2/L3
BD12500	12	50	229	138	208	213	16	T3/L3
BD12550	12	55	229	138	208	213	17.5	T3/L3
BD12600	12	60	260	169	211	216	18.5	T3/L11

BD12650	12	65	350	167	182	182	23.4	T3
BD12650A	12	65	350	166	174	174	20.5	T3/L9
BD12650B	12	65	330	173	167	170	20.8	T2
BD12700	12	70	260	169	211	216	21.5	T3/L11
BD12700S	12	70	350	167	179	179	21.5	T3
BD12750	12	75	260	169	211	216	22.5	T3/L11
BD1275S	12	75	350	167	179	179	22.5	T3
BD12800	12	80	350	167	179	179	24	F5/F11
BD12800A	12	80	260	169	211	216	23.5	T3/L11
BD12850	12	85	307	169	210	215	26	F12/F15
BD12900	12	90	307	169	210	215	28.5	T3
BD121000	12	100	330	171	214	220	30	T4/L5
BD121000A	12	100	406	173	208	238	30.5	T5/L14
BD121000S	12	100	407	177	225	225	31	T5
BD121000V	12	100	307	169	210	215	29.5	T3
BD121200	12	120	407	177	225	225	35	T5
BD121200A	12	120	406	173	208	238	35	T5/L14
BD121340	12	134	340	173	280	287	42	T5
BD121500	12	150	483	170	241	241	44.5	T4/L15
BD121600	12	160	532	206	215	219	50	T4/L17
BD121800	12	180	532	206	215	219	53	T4/L17
BD122000	12	200	522	238	218	223	60	T4/L17
BD122250	12	225	522	238	218	223	65	T4/L17
BD122300	12	230	521	269	204	209	67	T5
BD122500	12	250	520	268	220	225	70	T5