



International Limited | Hong Kong

BRAND: BIOD PRO

High Rate Batteries

Note: Technical specifications are subject to change without prior notice. The table provides standard characteristics; however, battery weight and dimensions may vary depending on regional regulations or specific customer requirements. For orders and inquiries, please contact us at hello@tevo.com.hk

01.01.2025

Model	Nominal Voltage	15 min. Rate (Watts/cell)	Capacity (AH)	Internal Resistance (mOhm)	Dimensions(mm)				Terminal	Weight
					Length	Width	Height	Total height		
					mm	mm	mm	mm		
HR619	6	19	4.5	15	70	47	101	107	F1/F2	0.8
HR622	6	22	5	12	70	47	101	107	F1/F2	0.9
HR631	6	31	7	9	151	34	94	100	F1/F2	1.28
HR634	6	34	9	8	151	34	94	100	F1/F2	1.35
HR651	6	51	12	6	151	50	94	100	F1/F2	2
HR1219	12	19	4.5	26	90	70	101	107	F1/F2	1.6
HR1222	12	22	5	22	90	70	101	107	F1/F2	1.8
HR1224	12	24	6	18	151	52	94	99	F1/F2	2.1
HR1231	12	31	7	20	151	65	94	100	F1/F2	2.45
HR1234	12	34	9	18	151	65	94	100	F1/F2	2.65
HR1251	12	51	12	11	151	98	95	101	F2	4
HR1276	12	76	18	12	181	77	167	167/167	T1/L1	5.7
HR1282	12	82	20	10	181	77	166	166	T1/L1	6.3
HR12100	12	100	24	10	166	175	125	125/125	T2/L6	8.2
HR12110	12	110	28	9	165	125	175	182/175	L13	9.3
HR12125	12	125	33	9	195	130	155	180/166	T3/L7	10.5
HR12160	12	160	45	7.5	197	165	170	170/170	T2/L3	14.2
HR12240	12	240	65	5.5	350	167	179	186/179	T3	21.5
HR12250	12	250	70	6	260	168	211	233/214	T3/L11	22
HR12282	12	282	75	5.5	260	168	211	233/214	T3/L11	23
HR12290	12	290	80	5	260	168	211	233/214	T3/L11	24.5
HR12330	12	330	90	4.5	306	169	211	233/214	T3L13	29.5
HR12390	12	390	100	3.5	330	171	214	220	T4	32.5
HR12425	12	425	120	3.2	409	176	225	225	T5	38
HR12475	12	475	134	3.5	342	172	280	285	T5	43

HR12500	12	500	140	3.2	342	172	280	285	T5	46
HR12535	12	535	150	3	485	172	240	242/240	T4/L15	47
HR12710	12	710	200	2.8	522	238	218	238/221	T4/L17	65
HR6710	6	710	200	3	321	176	226	229	T5	32.5