



International Limited | Hong Kong

BRAND: BIOD PRO

OPzV Batteries

Note: Technical specifications are subject to change without prior notice. The table provides standard characteristics; however, battery weight and dimensions may vary depending on regional regulations or specific customer requirements. For orders and inquiries, please contact us at hello@tevo.com.hk

01.01.2025

Model	Nominal Voltage (V)	Nominal Capacity (AH/10HR)	Battery Dimension				Weight (Approx.)	Terminal Type
			Length	Width	Height	Total Height		
			mm	mm	mm	mm	kg	
OPzV2-150	2	150	103	206	354	390	15.4	T5
OPzV2-200	2	200	103	206	354	390	17	T5
OPzV2-250	2	250	124	206	354	390	20.3	T5
OPzV2-300	2	300	145	206	471	506	24.4	T5
OPzV2-350	2	350	124	206	471	506	27.5	T5
OPzV2-420	2	420	145	206	471	506	32.5	T5
OPzV2-500	2	500	166	206	471	506	37	T5
OPzV2-600	2	600	145	206	646	681	44.2	T5
OPzV2-700	2	700	254	210	471	506	52	T5
OPzV2-770	2	770	254	210	471	506	54	T5
OPzV2-800	2	800	191	210	646	681	60	T5
OPzV2-1000	2	1000	233	210	646	681	73.2	T5
OPzV2-1200	2	1200	275	210	646	681	87	T5
OPzV2-1500	2	1500	275	210	796	831	106.5	T5
OPzV2-2000	2	2000	399	212	772	807	144	T5
OPzV2-2500	2	2500	487	212	772	807	185	T5
OPzV2-3000	2	3000	576	212	772	807	220	T5
OPzV2-1500	2	1500	275	210	796	831	106.5	T5

OPzV2-2000	2	2000	399	212	772	807	144	T5
OPzV2-2500	2	2500	487	212	772	807	185	T5
OPzV2-3000	2	3000	576	212	772	807	220	T5
OPzV12-45	12	45	260	169	211	218	18	T3
OPzV12-60	12	60	260	169	211	218	23	T3
OPzV12-80	12	80	328	172	215	220	30	T4
OPzV12-100	12	100	407	177	225	225	36	T4
OPzV12-120	12	120	483	170	241	241	45.9	T4
OPzV12-140	12	140	532	207	214	219	53.5	T4
OPzV12-160	12	160	532	207	214	219	57	T4
OPzV12-180	12	180	522	240	219	224	66.5	T4
OPzV12-200	12	200	521	262	220	225	73	T5